9MM PALLAS ULTIMATE FLOORING

PRODUCT DATA

Size	1800 x 228mm
Thickness	9.0mm with underlay (2mm)
Locking system	2G/2G
Wear layer	0.5mm – Polyurethane (PU) with Star Coating ®
Surface finish	Wood emboss, 8%- 12% Gloss
Bevelled edge	Yes – all sides 20 degrees
Mass per unit area	4 planks per pack – 1.642M^2
Wear Surface	20yr Domestic – 10yr Commercial

TECHNICAL DATA

Standards	Test Method	Test Result
Standards	ISO14001, SGS, TUV (LGA)	
Wear Group Classification	ISO 10874 Commercial ISO 10874 Domestic	Heavy Domestic, Heavy Commercial
Thermal resistance (Dimensional stability and curling after exposure to heat)	With reference to BN EN ISO 24345:2012	Manufacturing direction: 0.06 Across-manufacturing direction:0.03 Curling: 0
Peel Resistance	BN EN ISO 24345:2012	Machine direction: avg value 80 Across-machine direction: avg value 75
Fire Resistance	EN ISO 9239-1:2010	Critical Flux (transverse and longitudinal) ≥ 11 kW/m^2 Smoke value ≤113% min
Staining and resistance to chemicals	EN ISO 26987:2012	Pass
Colour fastness to light	EN ISO 105-B02:2014	Pass
Wear resistance	EN 660-2:1999+A1:2003 and EN 649:2011	Wear Group: T
Acoustic impact noise reduction	ISO 16283-2:2015 & 717-2:2013 Requirement of ≤ 62 dB	41dB
Residual Indentation	EN ISO 24343-1:2012	Pass
Castor chair continuous use	EN 425:2002	Pass
Slip resistance*	DIN 51130:2014-02	Test Result R10 — Pass
Wet Slip test	AS 4586:2013 Appendix A	Class: P3 – Pass
Toxic elements test	EN71	Part3: Pass (No lead or heavy metals)
Phthalate free		Yes

Contact: Chameleon Flooring. 29 Loam Street, Acacia Ridge QLD 4110